



## Concrete Buckets

### Camlever Standard Buckets

The industry standard features high strength, light weight tubular construction. A variable-leverage gate gives the operator complete control from a trickle to one yard per second of one inch slump concrete.



Model	Width	Width	Load	Overall	Gate	Weight	Capacity
	OD	ID	Height	Height	Diameter	Lbs.	Yd.
CL-050	46"	43"	35"	51"	21"	315	1/2
CL-075	46"	43"	42"	60"	21"	340	3/4
CL-100	56"	52"	46"	63"	24"	435	1
CL-150	64"	60"	52"	72"	24"	550	1-1/2
CXL-200	71"	65"	57"	80"	32"	870	2
CXL-300	76"	70"	67"	90"	32"	1125	3
CXL-400	88"	82"	73"	108"	32"	1450	4
CXL-500	88"	82"	82"	114"	32"	1500	5

Optional Air Operated Gates 185 Lbs.

### Camlever Low Boy Buckets

Minimum height for easy loading. Two yard model is seven inches lower than an ordinary bucket of the same capacity. Gate opening and handle are parallel to the direction of the form to aid pouring in narrow forms. Low Boys have all of the advantages of the Standard Buckets but with a lower profile.



Model	Width	Width	Load	Overall	Gate	Weight	Capacity
	OD	ID	Height	Height	Diameter	Lbs.	Yd.
LB-0375	38"	36"	32"	42"	20"	214	3/8
LB-050	46"	43"	36"	46"	20"	226	1/2
LB-075	46"	43"	40"	54"	20"	325	3/4
LB-100	56"	52"	41"	58"	24"	530	1
LXB-150	64"	60"	48"	68"	30"	755	1-1/2
LXB-200	71"	65"	55"	72"	30"	880	2
LXB-300	76"	70"	61"	86"	30"	1200	3
LXB-400	88"	82"	65"	100"	30"	1500	4

Optional Air Operated Gates 185 Lbs.

BELOW THE HOOK

### Top Ring Extensions



Model	Bucket	Added	Weight
	Size	Capacity	Lbs.
TR-050	1/2	1/4 Yd.	30
TR-075	3/4	1/4 Yd.	45
TR-100	1	1/4 Yd.	70
TR-150	1-1/2	1/4 Yd.	80
TR-200	2	1/2 Yd.	90
TR-300	3	1/2 Yd.	155
TR-400	4	5/8 Yd.	180

### Bucket Boots



Model	Length	Disc.	Weight
		Diameter	Lbs.
RU-1	36"	8"	40
RU-2	36"	12"	40
RU-3	72"	8"	60
RU-4	42"	16"	55

Models RU-1, 2 and 3 fit 18", 21" and 24" gate.  
Model RU-4 fits 32" gate.

### Side Dump Chutes



Model	Bucket	Weight	Length
	Size	Lbs.	
SCL-375	3/8	50	48"
SCL-050	1/2	50	48"
SCL-075	3/4	60	48"
SCL-100	1	70	72"
SCL-150	1-1/2	70	72"
SCL-200	2	85	72"
SCL-300	3	90	72"
SCXL-232	2	90	82"
SCXL-332	3	100	96"
SCXL-432	4	105	96"

### Boot Extensions



Model	Length	Diameter	Weight
			Lbs.
RU-5	8"	8"	40
RU-6	10"	12"	55